

Leak-Finder

Leakage Pinpointing System



Halma Water Management



Introduction

Leak-Finder is an innovative system specifically designed to provide accurate and reliable leakage pinpointing in traditionally difficult leak

detection situations, such as on plastic pipelines.

Leak-Finder allows operators to pinpoint the leak position and therefore speed repair and reduce excavation costs to a minimum. The system is primarily designed for Customer Side Leakage (CSL), but equally applicable to other pipe applications within the designated range.

The system is designed to work on pipe with a smooth internal bore up to a diameter of up to 50mm.



Deployment

Leak-Finder is connected to an open end, or fitting of the test pipe using a section of MDPE. The hose is reeled through the Leak-Finder control and inflation unit into the end of the pipe, with an appropriate bladder in place. The operator inflates the bladder to block a chosen section of the pipe; this section is then pressurised from the pump at the central unit. Control unit dials indicate whether the test section is holding pressure or failing, thereby establishing whether or not a leak is present. The bladder is easily deflated and moved, to change the section under test and to accurately pinpoint the exact position of the leak.

The operator knows exactly the length for connection point to the leak. Accessory options are available to trace the run if necessary.

Scope of Supply

Leak-Finder is supplied with standard equipment as follows:

- Control unit with integral manual pump, and indication dials
- Reel with 50m of plastic tube for insertion and inflation of the bladder
- Standard set of bladders for pipe up to 50mm diameter pipes
- Hose connection from control unit to reel
- Operating Manual.



For more information call +44 (0) 1633 489479
or visit www.hwm-water.com

Company is ISO 9001 Registered No.06134A

A HALMA COMPANY